





Pitch:5.0/10.0mm

MODEL:JL305V

认证/CERTIFICATION	
------------------	--

材质及电镀		
螺丝	M2.5, 钢, 镀锌	
弹片	磷青铜, 镀镍	
方针	黄铜, 镀锡	
塑件	PBT, UL94V-0	
电气性能		
参考标准	UL	IEC
额定电压	250V	250V
额定电流	16A	17.5A
使用线径	22-14AWG	2.5mm ²
接触电阻	20mΩ	
绝缘电阻	500MΩ/DC500V	
耐电压	AC2000V/1Min	
机械性能		
温度范围	-30℃~+120℃	
瞬时温度	+250℃ 5秒	
扭矩	4.08kgf-cm/0.4Nm/3.54Lbin	
剥线长度	4.5-5mm	

MATERIAL	
Screws	M2.5 Steel Zn plated
Shrapnel	Phosphor bronze, Ni plated
Pin header	Brass, Sn plated
Housing	PBT, UL94V-0
ELECTRICAL	
Standard	UL IEC
Rated voltage	250V 250V
Rated current	16A 17.5A
Wire range	22-14AWG 2.5mm ²
Contact resistance	20mΩ
Insulation resistance	500MΩ/DC500V
Withstanding voltage	AC2000V/1Min
MECHANICAL	
Temp. range	-30°C~+120°C
Max. soldering	+250°C 5 Sec
Torque	4.08kgf-cm/0.4Nm/3.54Lbin
Strip length	4.5-5mm



P.C.B. LAYOUT

