



Pitch:3.5mm

MODEL:JL350C

认证/CERTIFICATION		CE	
材质及电镀			
螺丝	M2.0, 钢, 镀锌		
弹片	磷青铜, 镀镍.		
方针	黄铜, 镀锡		
塑件	PA66, UL94V-0		
电气性能			
参考标准	UL	IEC	
额定电压	300V	130V	
额定电流	10A	10A	
使用线径	24-18AWG	1.0mm ²	
接触电阻	20mΩ		
绝缘电阻	500MΩ/DC500V		
耐电压	AC2000V/1Min		
机械性能			
温度范围	-40℃~+105℃		
瞬时温度	+250℃ 5秒		
扭矩	2.04kgf-cm/0.2Nm/1.77Lbin		
剥线长度	4.5-5mm		
MATERIAL			
Screws	M2.5 Steel Zn plated		
Shrapnel	Phosphor bronze, Ni plated		
Pin header	Brass, Sn plated		
Housing	PA66, UL94V-0		
ELECTRICAL			
Standard	UL	IEC	
Rated voltage	300V	130V	
Rated current	10A	10A	
Wire range	24-18AWG	1.0mm ²	
Contact resistance	20mΩ		
Insulation resistance	500MΩ/DC500V		
Withstanding voltage	AC2000V/1Min		
MECHANICAL			
Temp. range	-40℃~+105℃		
Max. soldering	+250℃ 5 Sec		
Torque	2.04kgf-cm/0.2Nm/1.77Lbin		
Strip length	4.5-5mm		

