



Pitch:5.0mm

MODEL:JL105R

认证/CERTIFICATION	
------------------	--

材质及电镀	
螺丝	M2.5, 钢, 镀锌
方块	黄铜, 镀镍
焊脚	黄铜, 镀锡
滑块	钢, 镀三价铬
塑件	PA66, UL94V-0
电气性能	
参考标准	UL IEC
额定电压	300V 450V
额定电流	20A 24A
使用线径	24-12AWG 2.5mm ²
接触电阻	20mΩ
绝缘电阻	500MΩ/DC500V
耐电压	AC2000V/1Min
机械性能	
温度范围	-40℃~+105℃
瞬时温度	+250℃ 5秒
扭矩	4.08kgf-cm/0.4Nm/3.54Lbin
剥线长度	12-13mm

MATERIAL	
Screws	M2.5 Steel Zn plated
Cage	Brass, Ni plated
Pin header	Brass, Sn plated
Cage	Steel Cr ³⁺ Zn plated
Housing	PA66, UL94V-0
ELECTRICAL	
Standard	UL IEC
Rated voltage	300V 450V
Rated current	20A 24A
Wire range	24-12AWG 2.5mm ²
Contact resistance	20mΩ
Insulation resistance	500MΩ/DC500V
Withstanding voltage	AC2000V/1Min
MECHANICAL	
Temp. range	-40℃~+105℃
Max. soldering	+250℃ 5 Sec
Torque	4.08kgf-cm/0.4Nm/3.54Lbin
Strip length	12-13mm

