



Pitch:10.0/10.16mm

MODEL:JL2EDGKM-10.0/10.16

认证/CERTIFICATION	
------------------	---

材质及电镀	螺丝 M3.0, 钢, 镀锌 夹片 磷青铜, 镀镍 方块 黄铜, 镀镍 塑件 PA66, UL94V-0	
电气性能		
参考标准	UL	IEC
额定电压	600V	750V
额定电流	15A	20A
使用线径	28~14AWG	2.5mm ²
接触电阻	20mΩ	
绝缘电阻	500MΩ/DC500V	
耐电压	AC2000V/1Min	
机械性能		
温度范围	-40℃~+105℃	
瞬时温度	+250℃ 5秒	
扭矩	5.10kgf-cm/0.5Nm/4.43Lbin	
剥线长度	7~8mm	

MATERIAL	Screws M3.0 Steel Zn plated Clamp Phosphor bronze, Ni plated Cage Brass, Ni plated Housing PA66, UL94V-0	
ELECTRICAL		
Standard	UL	IEC
Rated voltage	600V	750V
Rated current	15A	20A
Wire range	28~14AWG	2.5mm ²
Contact resistance	20mΩ	
Insulation resistance	500MΩ/DC500V	
Withstanding voltage	AC2000V/1Min	
MECHANICAL		
Temp. range	-40℃~+105℃	
Max. soldering	+250℃ for 5 Sec	
Torque	5.10kgf-cm/0.5Nm/4.43Lbin	
Strip length	7~8mm	

