



Pitch:5.0/5.08mm

MODEL:JL2EDGKAM-5.0/5.08

|                  |                                                                                     |
|------------------|-------------------------------------------------------------------------------------|
| 认证/CERTIFICATION |  |
|------------------|-------------------------------------------------------------------------------------|

|       |                           |                    |
|-------|---------------------------|--------------------|
| 材质及电镀 |                           |                    |
| 螺丝    | M3.0, 钢, 镀锌               |                    |
| 夹片    | 磷青铜, 镀镍                   |                    |
| 方块    | 黄铜, 镀镍                    |                    |
| 塑件    | PA66, UL94V-0             |                    |
| 电气性能  |                           |                    |
| 参考标准  | UL                        | IEC                |
| 额定电压  | 300V                      | 450V               |
| 额定电流  | 15A                       | 20A                |
| 使用线径  | 28~14AWG                  | 2.5mm <sup>2</sup> |
| 接触电阻  | 20mΩ                      |                    |
| 绝缘电阻  | 500MΩ/DC500V              |                    |
| 耐电压   | AC2000V/1Min              |                    |
| 机械性能  |                           |                    |
| 温度范围  | -40℃~+105℃                |                    |
| 瞬时温度  | +250℃ 5秒                  |                    |
| 扭矩    | 5.10kgf-cm/0.5Nm/4.43Lbin |                    |
| 剥线长度  | 7-8mm                     |                    |

|                       |                            |                    |
|-----------------------|----------------------------|--------------------|
| MATERIAL              |                            |                    |
| Screws                | M3.0 Steel Zn plated       |                    |
| Clamp                 | Phosphor bronze, Ni plated |                    |
| Cage                  | Brass, Ni plated           |                    |
| Housing               | PA66, UL94V-0              |                    |
| ELECTRICAL            |                            |                    |
| Standard              | UL                         | IEC                |
| Rated voltage         | 300V                       | 450V               |
| Rated current         | 15A                        | 20A                |
| Wire range            | 28~14AWG                   | 2.5mm <sup>2</sup> |
| Contact resistance    | 20mΩ                       |                    |
| Insulation resistance | 500MΩ/DC500V               |                    |
| Withstanding voltage  | AC2000V/1Min               |                    |
| MECHANICAL            |                            |                    |
| Temp. range           | -40℃~+105℃                 |                    |
| Max. soldering        | +250℃ for 5 Sec            |                    |
| Torque                | 5.10kgf-cm/0.5Nm/4.43Lbin  |                    |
| Strip length          | 7~8mm                      |                    |

