



Pitch:7.50/7.62mm

MODEL:JL2EDGKB-7.5/7.62

认证/CERTIFICATION

材质及电镀

螺丝	M3.0, 钢, 镀锌
夹片	磷青铜, 镀镍
方块	黄铜, 镀镍
塑件	PA66, UL94V-0

电气性能

参考标准	UL	IEC
额定电压	300V	450V
额定电流	15A	20A
使用线径	28~14AWG	2.5mm ²
接触电阻	20mΩ	
绝缘电阻	500MΩ/DC500V	
耐电压	AC2000V/1Min	

机械性能

温度范围	-40℃~+105℃	
瞬时温度	+250℃ 5秒	
扭矩	5.10kgf-cm/0.5Nm/4.43Lbin	
剥线长度	7~8mm	

MATERIAL

Screws	M3.0 Steel Zn plated
Clamp	Phosphor bronze, Ni plated
Cage	Brass, Ni plated
Housing	PA66, UL94V-0

ELECTRICAL

Standard	UL	IEC
Rated voltage	300V	450V
Rated current	15A	20A
Wire range	28~14AWG	2.5mm ²
Contact resistance	20mΩ	
Insulation resistance	500MΩ/DC500V	
Withstanding voltage	AC2000V/1Min	

MECHANICAL

Temp. range	-40℃~+105℃	
Max. soldering	+250℃ for 5 Sec	
Torque	5.10kgf-cm/0.5Nm/4.43Lbin	
Strip length	7~8mm	

