



Pitch:5.0mm

MODEL:JL211V-5.0

认证/CERTIFICATION

材质及电镀

|    |               |
|----|---------------|
| 弹片 | 不锈钢           |
| 焊针 | 黄铜, 镀锡        |
| 塑件 | PA66, UL94V-0 |

电气性能

|      |              |                    |
|------|--------------|--------------------|
| 参考标准 | UL           | IEC                |
| 额定电压 | 300V         | 250V               |
| 额定电流 | 10A          | 15A                |
| 使用线径 | 26-16AWG     | 1.5mm <sup>2</sup> |
| 接触电阻 | 20mΩ         |                    |
| 绝缘电阻 | 500MΩ/DC500V |                    |
| 耐电压  | AC2000V/1Min |                    |

机械性能

|      |            |
|------|------------|
| 温度范围 | -40℃~+105℃ |
| 瞬时温度 | +250℃ 5秒   |
| 剥线长度 | 8-9mm      |

MATERIAL

|            |                  |
|------------|------------------|
| Wire guard | Stainless steel  |
| Pin header | Brass, Sn plated |
| Housing    | PA66, UL94V-0    |

ELECTRICAL

|                       |              |                    |
|-----------------------|--------------|--------------------|
| Standard              | UL           | IEC                |
| Rated voltage         | 300V         | 250V               |
| Rated current         | 10A          | 15A                |
| Wire range            | 26-16AWG     | 1.5mm <sup>2</sup> |
| Contact resistance    | 20mΩ         |                    |
| Insulation resistance | 500MΩ/DC500V |                    |
| Withstanding voltage  | AC2000V/1Min |                    |

MECHANICAL

|                |             |
|----------------|-------------|
| Temp. range    | -40℃~+105℃  |
| Max. soldering | +250℃ 5 Sec |
| Strip length   | 8-9mm       |

